

****IMPORTANT: Read all instructions before beginning application process****



InvisiTread Detailed Application Instructions

Tools Required:

Trigger Sprayer, Microfiber Spreader or Garden style Pump Sprayer
(Pump sprayer recommended for larger areas)
Two, 5 gallon pails/buckets – clean
Sponge Mop or Wet-Dry Vacuum/Extraction Tool (recommended)
Deck Brush (for pre-application cleaning, if needed)

****PRE-APPLICATION TESTING****

Utilize steps 1 – 4 below on a small hidden area, or extra tile to determine dwell time for your particular surface and desired traction. In general, longer dwell time equals higher traction. Start with 6 minutes of dwell and work up to no more than 16 minutes. Occasionally, 2 applications are needed to increase traction to desired levels, rinse/extract 1st application & repeat steps 2-4.

Pre-application set-up

- In 1st 5 gallon bucket, mix 6 oz. Traction Wash per gallon of water, a 1:20 dilution. Use a higher concentration (up to 12 oz/gal) if very dirty or greasy. Set aside remaining solution for RINSE step.
- Fill sprayer (or 2nd bucket, if spreading instead of spraying) with 1 gallon of InvisiTread per 400 sqft. *Do not dilute InvisiTread. Do not mix chemicals.*

Application Process

- Step 1: CLEAN.** Clean the floor very well with the Traction Wash solution. If necessary, use the deck brush to scrub the tile & grout for very dirty floors. Rinse the floor with clean water and dry. Use a wet dry vacuum or extraction tool, if available. It is ok to leave the grout joints wet or damp.
- Step 2: APPLY.** Spray or spread the InvisiTread onto the area to be treated. Use a liberal amount of product. Coverage should not be about 400 sq. ft per gallon.
- Step 3: DWELL.** Allow InvisiTread to dwell for 6 – 16 min (exact time shall be determined by your pre-application testing). Keep surface saturated with product during the entire dwell time. DO NOT allow to dry out, puddle or run off. Apply more InvisiTread, as needed.
- Step 4: RINSE.** After dwell time has elapsed pour 1:20 Traction Wash dilution onto the tile and scrub grout joints with brush to break up residue. Extract surface. Rinse a 2nd time with clean water and then extract surface. Surface is ready for immediate use.

*****Test traction by wetting the surface with clean water and trying to slide foot.
If more traction is desired, do a 2nd application, repeat steps 2 - 4.*****

Clean regularly with Traction Wash™ @ 1:32 dilution, to maintain your enhanced Coefficient Of Friction (COF).

Troubleshooting - if necessary

After grout has completely dried out you might notice some white residue form in a few spots over the next few days. This is simply a salt residue left over after application; it is not harmful and will be removed with regular cleaning over the next few days. To remove right away, scrub with 1:4 dilution of vinegar to water, or 1:32 dilution of TractionWash to water. NOTE: This does not occur on every application or every type of grout.

Contact customer service at 888-842-3356 with any questions.



Company Profile:

Surface Solutions, LLC

Industry:

Surface Engineering
Consulting
Slip Resistant Treatments
Anti-Graffiti Treatments

Website:

www.InvisiTread.com
www.TotalSurfaceSolution.com

Corporate Address:

515 Valley St.
Suite 130
Maplewood, NJ 07040

Contact:

support@totalsurfacesolution.com
888-842-3356